

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
31 July 2003 (31.07.2003)

PCT

(10) International Publication Number  
**WO 03/062834 A1**

(51) International Patent Classification<sup>7</sup>: **G01P 3/487**,  
G01D 5/14; 5/245

(21) International Application Number: PCT/NL03/00048

(22) International Filing Date: 23 January 2003 (23.01.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
1019828 24 January 2002 (24.01.2002) NL

(71) Applicant (for all designated States except US): **AB SKF**  
[SE/SE]; Hornsgatan 1, S-415 50 Göteborg (SE).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **MOL, Hendrik, Anne** [NL/NL]; Rijkssstraatweg 54, NL-4254 XG Sleetwijk (NL). **DUITS, Johannes, Andrianus, Maria** [NL/NL]; Zuwe 50, NL-2411 ZK Bodegraven (NL).

(74) Agent: **VAN WESTENBRUGGE, Andries**; Nederlandsch Octrooibureau, Scheveningsweg 82, P.O. Box 29720, NL-2502 LS The Hague (NL).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

[Continued on next page]

(54) Title: ROTATIONAL SPEED SENSOR



(57) Abstract: Rotational speed sensor (10) comprising a rotatable ring (11), e.g. connectable to a bearing. The rotational speed sensor has K magnetic pole pairs (12) distributed angularly over the rotatable ring (11). Also, sensor means are present positioned relative to the rotatable ring such that a varying magnetic field is detected by the sensor means. The sensor means comprise a first pair of magnetic sensors (15, 16), the first pair of magnetic sensors (15, 16) being positioned  $2\pi L/K$  radians apart from each other. The sensor means may further comprise a second pair of magnetic sensors (17, 18), the second pair of sensors (17, 18) being positioned  $2\pi M/K$  radians apart from each other. The first pair of sensors (15, 16) and second pair of sensors (17, 18) are positioned at a relative position of  $(2\pi/K)*((2n-1)/2)$  radians.

WO 03/062834 A1